

Adjustable Liquid Flow Switch

DS1433



www.platon-direct.eu

Features:

- Compact
- Good repeatability
- Dirt resistant
- High switch capability
- Hermetic separation of mechanical and electrical components

Description:

Using a spring loaded variable orifice flow meter technique, the sensor can be installed at any angle and can operate at high pressures and temperatures. The moving element trips an external reed sensor, which itself can be adjusted along a flow scale.

Pipe Connections	1/4" - 1" BSP
Flow Range	0.4 - 40 L/min
Body	MI Models - Brass; KI Models - Stainless Steel
Seals	MI Models- Buna N; KI Models - Viton
Pressure	200 bar max
Temperature	120°C max
Cable	2.5m long IP65 termination
Output	SPCO 250Vac VA 1.5 Amps
Pressure Drop	0.5 bar at max flow
Length	MR8-20 109mm MR25 135mm

Explosion Proof Flow Switch

DS1432

SKU	Description
FMR10KI	Flow Switch Adjustment 0.4 - 4 L/min with 3/8" BSP Stainless Steel Pipe Connection
FMR10MI	Flow Switch Adjustment 0.4 - 4 L/min with 3/8" BSP Brass Pipe Connection
FMR15KI	Flow Switch Adjustment 1 - 10 L/min with 1/2" BSP Stainless Steel Pipe Connection
FMR15MI	Flow Switch Adjustment 1 - 10 L/min with 1/2" BSP Brass Pipe Connection
FMR20KI	Flow Switch Adjustment 5 - 20 L/min with 3/4" BSP Stainless Steel Pipe Connection
FMR20MI	Flow Switch Adjustment 5 - 20 L/min with 3/4" BSP Brass Pipe Connection
FMR25KI	Flow Switch Adjustment 10 - 40 L/min with 1" BSP Stainless Steel Pipe Connection
FMR25MI	Flow Switch Adjustment 10 - 40 L/min with 1" BSP Brass Pipe Connection
FMR8KI	Flow Switch Adjustment 0.4 - 4 L/min with 1/4" BSP Stainless Steel Pipe Connection
FMR8MI	Flow Switch Adjustment 0.4 - 4 L/min with 1/4" BSP Brass Pipe Connection



LICO Electronics GmbH
lederinger Strasse 31
A-2320 Kledering, Austria
E-mail: sales@lico.at | office@lico.at
Tel.: +43 1 706 4300

LICO Mechatronic Kft.
Raba u. 4.
H-2030 Erd, Hungary
Email: sales@lico.hu / sales@lico.at
Tel: +36 23 520 138

www.platon-direct.eu